





























Materials

Housing: Painted Steel Panel Legend: Polycarbonate

Standard Colour: White Ral 9016

Black - RAL 9017 Alternative Colour: Add /BL to order code

Warranty

Standard Warranty: 6 Years Alternative Warranty: 10 Years

Add /10Y to order code

Order Code	EX/LED/230S **			
Mode of operation	Slave			
Input voltage	230/240V (207Vac - 264Vac) 50/60Hz			
Power consumption	6VA, I _{nom} = 0.025A			
Lamp	12x Samsung White LED			
Lamp Life	L ₈₀ B ₅₀ 80000 Hours			
Nominal lamp current	I _{rated} = 0.35A			
Nominal lamp power	P _{rated} = 1W			
Degree of protection	IP40 - for indoor use only.			
Cable entry	Two 20mm conduit points on top of fitting, single 20mm conduit point on either side, and rear BESA terminal box mounting			
Luminaire class	Class I			
Weight	1.6kg			
Packaging Weight	0.161kg			
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13 EN 60598-2-22			
Environment	0°C to 45°C up to 80% relative humidity.			

System	Order Code	Mode of	Battery	Battery P/N	Viewing Distance	Dimensions (mm)			
		Operation				Α	В	С	
Central Battery	EX/LED/230S **	Slave	n/a	n/a	36 Metres	430	201	60	
Alternative Systems Available:									
Standalone	EXM3/LED **	Maintained	4.8V 1.3Ah NiMh	70229	36 Metres	430	201	60	
DALI	EXM3/LED/**/DA	Maintained	3.6v 2.1Ah NiMh	70251	36 Metres	430	201	60	
DALI Central Battery	ZEXLED230S**DA	Slave	n/a	n/a	36 Metres	430	201	60	

Alternative Legends



Replace ** with 01 for application of Left Arrow PN: 01710



Replace ** with 02 for application of Down Arrow PN: 01733



Replace ** with 03 for application of Right Arrow PN: 01754



Replace ** with 04 for application of Up Arrow PN: 01775