



IP 40	6Y Warranty	6500K	Ceiling Mounted
28m Viewing Distance	2.3 Kg	NiMh Battery	Class I

Order Code	VAIM3/LED/CM**
Emergency duration	3 hours
Input voltage	230/240V (207Vac - 264Vac) 50/60Hz
Power consumption	5VA
Battery	Rechargeable 4.8V 1.3Ah NiMh
Battery charger	Constant Current Nominal charge 0.5A
Battery low voltage cut off	4.0Vdc
Battery discharge current @ 4.8Vdc	0.28A
Battery discharging limits	up to 0.4A for 3 hours
Lamp	8 x High Powered White Samsung LEDs
Lamp Life	$L_{80}^{B50}$ 80000 Hours
Nominal lamp current	$I_{rated} = 0.35A$
Nominal lamp power	$P_{rated} = 1W$
Cable entry	20mm Rear entry
Luminaire class	Class I
Weight	2.1 kg
Packaging Weight	0.15 kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 45°C up to 80% relative humidity.

### Materials

Housing: Painted Steel  
 Panel Legend: Acrylic

Standard Colour : \*\*White -Add **WH** to order code  
 Alternative Colours: \*\*Black -Add **BL** to order code  
 \*\*Brushed Chrome- Add **BCH** to order code

### Warranty

Standard Warranty: 6 Years  
 Alternative Warranty: 10 Years  
 Add **/10Y** to order code

System	Order Code	Mode of Operation	Battery	Battery P/N	Viewing Distance	Dimensions (mm)			
						A	B	C	D
Standalone	VAIM3/LED/CM**	Maintained	4.8V 1.3Ah NiMh	70229	28 Metres	365	325	90	50
Alternative Systems Available:									
Central Battery	ZVAILED**230S	Slave	n/a	n/a	28 Metres	365	325	90	50
DALI	ZVAIM3LEDCM**DA	Maintained	3.6V 4.5Ah NiMh	70272	28 Metres	365	325	90	50

### Legends (Ordered Separately)



Left /Right Arrow (Left one side, Right opposite side)  
 PN: LPSTISO13MVL

Down Arrow (both sides)  
 PN: LPSTISO02MVL

Up Arrow (both sides)  
 PN: LPSTISO04MVL

**Additional options of Printed Panels available. Contact Ventilux for further details.**